TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 23 Dec 2014 20:07:01 Local Analysis complete: 23 Dec 2014 21:26:02 Local

Data Conversion Analysis Report

Observation start time: 19 Dec 2014 11:15:29 UTC Duration of observation: 59.976 real-time seconds

Data directory: V:\Observation Records\2014 12 19 Io-B\2014-12-19_34_CH01\Folder.00001

Number of digitized input files: 153

First input filename: AS_CH01-001.sig Last input filename: AS_CH01-153.sig

Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz

Digitized burst file duration: 209.696 ms

Digitized burst cycle time: 392 ms
Dead time between data bursts: 182.304 ms

Digitization soverage: E2 4020 persont

Digitization coverage: 53.4939 percent

FFT bins: 2048 FFT sweep time: 204.8 *µ*s

, burct: 1022

FFT sweeps per digitized data burst: 1023

Dead FFT sweeps between each digitized data burst: 889

FFT sweeps per digitized data burst including dead time padding: 1912

adding: 1912 adding: 292536

Total FFT sweeps for 153 input files, including padding: 292536

FFT BW: 5 MHz FFT RBW: 4.88281 kHz

FFT Windowing: None (uniform window)
FFT display low frequency: 2.8 MHz (FFT bin # 574)

FFT display high frequency: 4.8 MHz (FFT bin # 984)

DC offset per FFT element zero: 8.59335 μ W (last FFT sweep of last data file)

DC offset applied to FFT before calculating dBm: 100 μ W

DC offset applied to FFT after calculating dBm: 11 dBm

SPS file detector sensitivity: 50 ADC counts per dB

Total FFT bins exported to SPS file: 411

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS output file name: V:\Observation Records\2014 12 19 Io-B\AJ4CO TWB 2014 12 19 - 034 - 11 15 29 .sps
SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second
SPS file start time: 19 Dec 2014 11:15:29.000 UTC
SPS file end time: 19 Dec 2014 11:16:28.911 UTC