TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 27 Jan 2015 10:57:57 Local Analysis complete: 27 Jan 2015 12:16:08 Local

Data Conversion Analysis Report

Observation start time: 20 Jan 2015 07:10:34 UTC Duration of observation: 59.976 real-time seconds

Data directory: V:\Observation Records\2015 01 20 Io-B\2015-01-20_36_CH01\Folder.00001

Number of digitized input files: 153

First input filename: AS_CH01–001.sig

Last input filename: AS_CH01–153.sig

Digitized burst file size: 2096961 samples per file

Digitized burst file sample rate: 10 MHz

Digitized burst file duration: 209.696 ms
Digitized burst cycle time: 392 ms

Dead time between data bursts: 182.304 ms

Digitization coverage: 53.4939 percent

Digitization coverage. 55.4959 percent

FFT bins: 2048 FFT sweep time: 204.8 μ s

hurct: 1022

FFT sweeps per digitized data burst: 1023

Dead FFT sweeps between each digitized data burst: 889

FFT sweeps per digitized data burst including dead time padding: 1912

Total FFT sweeps for 153 input files including padding: 292536

Total FFT sweeps for 153 input files, including padding: 292536

FFT BW: 5 MHz

FFT RBW: 4.88281 kHz
FFT Windowing: None (uniform window)

FFT display low frequency: 2.8 MHz (FFT bin # 574)

FFT display high frequency: 4.8 MHz (FFT bin $\mbox{\em \#}$ 984) Total FFT bins exported to SPS file: 411

DC offset per FFT element zero: 9.39157 μ W (last FFT sweep of last data file)

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to FFT before calculating dBm: 100 μ W

DC offset applied to FFT after calculating dBm: 11 dBm

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS output file name: V:\Observation Records\2015 01 20 Io-B\AJ4CO TWB 2015 01 20 - 035 - 07 10 34 .sps

SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 20 Jan 2015 07:10:34.000 UTC SPS file end time: 20 Jan 2015 07:11:33.911 UTC