## TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 28 Jan 2015 05:11:20 Local Analysis complete: 28 Jan 2015 06:31:16 Local

## **Data Conversion Analysis Report**

Observation start time: 20 Jan 2015 07:42:28 UTC Duration of observation: 59.976 real-time seconds

Data directory: V:\Observation Records\2015 01 20 Io-B\2015-01-20\_52\_CH01\Folder.00001

Number of digitized input files: 153 First input filename: AS\_CH01–001.sig Last input filename: AS\_CH01–153.sig

Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182.304 ms Digitization coverage: 53.4939 percent

FFT bins: 2048 FFT sweep time: 204.8 µs FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536

> FFT BW: 5 MHz FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin # 574 ) FFT display high frequency: 4.8 MHz (FFT bin # 984 ) Total FFT bins exported to SPS file: 411

DC offset per FFT element zero: 9.13044  $\mu$ W (last FFT sweep of last data file) DC offset applied to FFT before calculating dBm: 100  $\mu$ W DC offset applied to FFT after calculating dBm: 11 dBm SPS file detector sensitivity: 50 ADC counts per dB DC offset applied to SPS data before export to SPS file: 1000 ADC counts

> SPS output file name: V:\Observation Records\2015 01 20 Io-B\AJ4CO TWB 2015 01 20 - 049 - 07 42 28 .sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 20 Jan 2015 07:42:28.999 UTC SPS file end time: 20 Jan 2015 07:43:28.911 UTC