TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 19 Dec 2014 23:17:22 Local Analysis complete: 20 Dec 2014 00:36:29 Local

Data Conversion Analysis Report

Duration of observation: 59.976 real-time seconds

Observation start time: 18 Dec 2014 09:59:10 UTC

Data directory: V:\Observation Records\2014 12 18 Io-C\2014-12-18_19_CH01\Folder.00001

Number of digitized input files: 153

First input filename: AS_CH01-001.sig Last input filename: AS_CH01-153.sig

Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz

Digitized burst file duration: 209.696 ms

Digitized burst cycle time: 392 ms Dead time between data bursts: 182.304 ms

Digitization coverage: 53.4939 percent

FFT sweep time: 204.8 μ s

FFT sweeps per digitized data burst: 1023

FFT bins: 2048

Dead FFT sweeps between each digitized data burst: 889

FFT sweeps per digitized data burst including dead time padding: 1912

Total FFT sweeps for 153 input files, including padding: 292536

FFT BW: 5 MHz FFT RBW: 4.88281 kHz

FFT Windowing: None (uniform window)

FFT display low frequency: 2.8 MHz (FFT bin # 574) FFT display high frequency: 4.8 MHz (FFT bin # 984)

Total FFT bins exported to SPS file: 411

DC offset per FFT element zero: 9.11966 μ W (last FFT sweep of last data file)

DC offset applied to FFT before calculating dBm: 100 μ W

DC offset applied to FFT after calculating dBm: 11 dBm

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 18 Dec 2014 09:59:10.000 UTC SPS file end time: 18 Dec 2014 10:00:09.911 UTC

SPS output file name: V:\Observation Records\2014 12 18 Io-C\AJ4CO TWB 2014 12 18 - 019 - 09 59 10 .sps